

Products: Malleable iron fittings

Brand: Jinan Meide

Malleable Iron M/F Elbow 45°

This malleable iron M/F Elbow 45° is a threaded pipe fitting designed to change the direction of a pipe run by 45 degrees, while connecting male and female threaded ends. It is used across a wide range of applications, including fire protection, plumbing, heating and ventilation systems.


Manufactured by Jinan Meide from high-quality malleable iron, this elbow fitting is produced to the relevant international standards BS EN 10242 and BS EN 10143 and is BSI kitemarked.

Taper threads are formed to ISO 7.1, helping to ensure a secure, reliable joint.

We supply M/F elbow fittings in self-colour or hot dip galvanised finishes, giving you flexibility for various installation requirements.



Dimensions and weights:



| Nominal bore (mm) | Nominal bore (inches) | Length: centre to face # dim. A (mm) | Length: centre to face dim. B (mm) | Weight each (kg) |
|-------------------|-----------------------|--------------------------------------|------------------------------------|------------------|
| 6 | 1/8 | 16 | 21 | 0.03 |
| 8 | 1/4 | 18.5 | 24 | 0.04 |
| 10 | 3/8 | 20 | 25 | 0.07 |
| 15 | 1/2 | 22 | 28 | 0.10 |
| 20 | 3/4 | 25 | 32 | 0.15 |
| 25 | 1 | 28 | 37 | 0.25 |
| 32 | 1 1/4 | 33 | 43 | 0.37 |
| 40 | 1 1/2 | 50 | 46 | 0.48 |
| 50 | 2 | 58 | 55 | 0.79 |
| 65 | 2 1/2 | 69 | 65 | 1.43 |
| 80 | 3 | 78 | 76 | 2.13 |
| 100 | 4 | 96 | 94 | 3.84 |

Order today:

01384 563 200

sales@cmt-engineering.co.uk

www.cmt-engineering.co.uk